

# hp Micron

Unique small controller and printer in one ideal for repeat printing jobs



# HP TIJ 2.5 technology

The HP 2.5 ® Micron is based upon reliable HP TIJ 2.5 technology which delivers consistent, high-quality, fast printing, exceptional value, and ease of use.

Micron is ideal for printing labels and for all cartons for food and pharmaceuticals. The possibilities are endless.

# Load print job from USB-key

Build your print job on a PC using the free MicroDraw software delivered with the printer. Transfer to USB-key and connect to your Micron printer and you are ready to print. The layout can be saved to the internal memory and the USB-key may be removed.

#### Easy to integrate and use

The Micron is an 'out of the box' unit. Place an inkcartridge in the head, connect to power and print instantly by pushing a button.

The printer takes up very little space. Not much more than the actual print cartridge itself. This makes it very easy to integrate.

Print horizontally or simply change the position of the printer 90° for printing vertically/down.

#### **Built-in sensor**

The Micron printer has an internal sensor. If external sensor is required connect this directly to the printer. The sensor distance is easily selected when designing the print job.



## 1/2" print height

The HP 2.5® Micron runs with 1 HP print cartridge allowing a print height of 12.7 mm.

#### **Ink Cartridges**

A wide range of inks for each application are available: spot colors, UV inks or fast drying inks. The printer allows parameters settings for each ink to reach the best performance in all situations.

#### Prints in 300 x 300 dpi

- Graphics
- Text(alphanumeric)
- Counters
- Barcodes(fixed)
- Date & Time(real-time&adjusted)
- 3 Windows true type fonts



# **Technical Details**

HP 2.5® MICRON MCHP1

## **Technology**

HP TIJ 2.5

#### **Print frequenzy**

15 KHz

#### **Print height**

Up to 12.7 mm / 1/2"

#### **Print heads**

1 pen integrated

#### **Print distance**

0.5-2.0mm(nozzletoprintsurface)

#### Voltage

15V(powersupplyincluded)

# **Design software**

microdraw(forw inpc)

#### Memory

1 print job in unit

#### **Print features**

Left/Right, Upside-down

#### **Layout features**

max.length2400px(~10cmin600dpi) Unicode support in text objectrotation(fixed):free objectrotation(variable):180deg Works with mm/inch/point/pixel

#### **Interface**

**USB 2.0** 

encoderinput3-33V(suBd9) in-/output3-33V(suBd9)

#### **Signals**

lowinksignal(diode) printsignal(diode) Built-in sensor

#### **Complies to**


CE directives

#### Housing

Stainless steel

#### Weight

0.53 kg / 1.17 lbs



#### **Resolution (Horizontal)**

Different resolutions can be chosen between 50 and 600 dpi.

The maximum speed is affected by selection of horizontal resolution, since the frequency of the printhead remains the same.

75 dpi max 302 m/min to 600 dpi max 38 m/min.


#### **Resolution (Vertical)**


Save ink costs by removing lines from the printed image. Available options are 300, 225, 200, and 150 DPI (0%,25%,33%,50%inkreduction).


Notice that because of print height being just 1/2", the number of active dots are 150 to 75.


#### **Accessories**

- usBkey(included)
- External sensor
- Encoder
- Bridges & Brackets
- mountings(inoconflK18mmincluded)











tel. 902 878 078 ventas@solge.es www.solge.es

